acc. to 29 CFR 1910.1200 App D

Schemenauer Distribution Quartz

Date of compilation: 2023-01-12

Version number: GHS 1.0 **SECTION 1: Identification** 1.1 **Product identifier** Schemenauer Distribution Quartz Trade name 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses Polymeric automobile paint sealant Vehicle coating Professional use Industrial use 3208.90.00. HS code 1.3 Details of the supplier of the safety data sheet Schemenauer Distribution LLC

Schemenauer Distribution LLC 651 Progress Way Sanford FL 32771

1-407-668-7831 schemenauerdistribution@gmail.com

1.4 Emergency telephone number

Emergency information service

USA 1.800.535.5053, INTL 1.352.323.3500 24 hour emergency number

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard state- ment
A.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
A.7	reproductive toxicity	2	Repr. 2	H361f
B.6	flammable liquid	3	Flam. Liq. 3	H226

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources. The mixture contains a substance that was identified as a PBT (persistent, bioaccumulative and toxic). The mixture contains a substance that was identified as vPvB (very persistent and very bioaccumulative).

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word warning
- Pictograms

GHS02, GHS07, GHS08



- Hazard statements

H226	Flammable liquid and vapor.
H315	Causes skin irritation.
H361f	Suspected of damaging fertility.

acc. to 29 CFR 1910.1200 App D

Schemenauer Distribution Quartz

Version number: GHS 1.0

Date of compilation: 2023-01-12

Precautionary stateme	ints
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	If on skin: Wash with plenty of water.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P308+P313	If exposed or concerned: Get medical advice/attention.
P321	Specific treatment (see on this label).
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

octamethylcyclotetrasiloxane

- Hazardous ingredients for labelling

2.3 Other hazards

Hazards not otherwise classified

May be harmful if swallowed (GHS category 5: acutely toxic - oral). Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

Containing a PBT-/vPvB-substance in a concentration of $\ge 0,1\%$.

Endocrine disrupting properties

Contains an endocrine disruptor (EDC) in a concentration of $\geq 0,1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
octamethylcyclotetrasiloxane	CAS No 556-67-2	40-<55	Repr. 2 / H361f Flam. Liq. 3 / H226
decamethylcyclopentasiloxane CAS No 541-02-6		12-<20	Flam. Liq. 4 / H227
Cyclosilazanes, di-Me, Me Hydro- gen, polymers with di-Me, Me hy- drogen silazanes, and 2,4-TDI	CAS No 2649792-57-2	12-<20	Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Flam. Liq. 2 / H225
Alkyl Polysilicates CAS No Trade Secret		3-<12	Acute Tox. 4 / H302 Skin Corr. 1B / H314
distillates (petroleum) hydrotreated, light CAS No 64742-47-8		3-<12	Asp. Tox. 1 / H304

acc. to 29 CFR 1910.1200 App D

Schemenauer Distribution Quartz

Version number: GHS 1.0

Date of compilation: 2023-01-12

Hazardous ingredients, Consideration of other advice

This table, if present, includes all GHS classified ingredients present above their cut-off limits, even if the finished product is not classified as hazardous by GHS.

Exact percentage of ingredients is withheld as a trade secret.

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

acc. to 29 CFR 1910.1200 App D

Schemenauer Distribution Quartz

6.1	Personal precautions, protective equipment and emergency procedures
	For non-emergency personnel Remove persons to safety.
	For emergency responders Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.
6.2	Environmental precautions Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.
6.3	Methods and material for containment and cleaning up
	Advice on how to contain a spill Covering of drains
	Advice on how to clean up a spill Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder
	Appropriate containment techniques Use of adsorbent materials.
	Other information relating to spills and releases Place in appropriate containers for disposal. Ventilate affected area.
6.4	Reference to other sections Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see sec- tion 10. Disposal considerations: see section 13.
SEC	TION 7: Handling and storage
7.1	Precautions for safe handling
	Recommendations
	- Measures to prevent fire as well as aerosol and dust generation Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take pre- cautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilat- ing/lighting/equipment. Use only non-sparking tools.
	- Specific notes/details
	Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particu- larly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form ex- plosive mixtures with air. Vapors may form explosive mixtures with air.
	Advice on general occupational hygiene
	Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment be- fore entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.
7.2	Conditions for safe storage, including any incompatibilities
	Managing of associated risks
	- Explosive atmospheres
	Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

Version number: GHS 1.0

SECTION 6: Accidental release measures

Date of compilation: 2023-01-12

acc. to 29 CFR 1910.1200 App D

Schemenauer Distribution Quartz

Version number: GHS 1.0

Date of compilation: 2023-01-12

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits) this information is not available

Relevant DNELs of components of the mixture						
Name of sub- stance	CAS No	End- point	Threshold level	Protection goal, route of expos- ure	Used in	Exposure time
octamethylcyclotet- rasiloxane	556-67-2	DNEL	73 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
octamethylcyclotet- rasiloxane	556-67-2	DNEL	73 mg/m ³	human, inhalatory	worker (industry)	acute - systemic ef- fects
octamethylcyclotet- rasiloxane	556-67-2	DNEL	73 mg/m ³	human, inhalatory	worker (industry)	chronic - local ef- fects
octamethylcyclotet- rasiloxane	556-67-2	DNEL	73 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
decamethylcyclo- pentasiloxane	541-02-6	DNEL	97 mg/m ³	human, inhalatory	worker (industry)	acute - systemic ef- fects
decamethylcyclo- pentasiloxane	541-02-6	DNEL	24 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
decamethylcyclo- pentasiloxane	541-02-6	DNEL	97 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
decamethylcyclo- pentasiloxane	541-02-6	DNEL	24 mg/m ³	human, inhalatory	worker (industry)	chronic - local ef- fects
Alkyl Polysilicates	Trade Secret	DNEL	14 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Alkyl Polysilicates	Trade Secret	DNEL	2 mg/kg bw/ day	human, dermal	worker (industry)	chronic - systemic effects

	-					
Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time
octamethylcyclotet- rasiloxane	556-67-2	PNEC	10 ^{mg} / _l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	0.059 ^{mg} / _{kg}	pelagic organisms	sediment	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	1.7 ^{mg} / _{kg}	(top) predators	water	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	0.44 ^{µg} / _l	aquatic organisms	freshwater	short-term (single instance)

acc. to 29 CFR 1910.1200 App D

Schemenauer Distribution Quartz

Version number: GHS 1.0

Г

Date of compilation: 2023-01-12

Relevant PNECs of components of the mixture						
Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time
octamethylcyclotet- rasiloxane	556-67-2	PNEC	0.044 ^{µg} / _l	aquatic organisms	marine water	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	10 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	3 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	0.3 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	0.59 ^{mg} / _{kg}	benthic organisms	sediment	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	0.16 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	10 ^{mg} / _l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	11 ^{mg} / _{kg}	benthic organisms	sediment	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	13 ^{mg} / _{kg}	(top) predators	water	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	1.1 ^{mg} / _{kg}	pelagic organisms	sediment	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	1.2 ^{µg} / _l	aquatic organisms	freshwater	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	0.12 ^{µg} / _l	aquatic organisms	marine water	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	10 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	11 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	1.1 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)
decamethylcyclo- pentasiloxane	541-02-6	PNEC	2.5 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

acc. to 29 CFR 1910.1200 App D

Schemenauer Distribution Quartz

Version number: GHS 1.0

Date of compilation: 2023-01-12

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid				
Color	clear				
Particle	not relevant (liquid)				
Odor	characteristic				

Other safety parameters

pH (value)	not determined			
Melting point/freezing point	not determined			
Initial boiling point and boiling range	>65 °C at 1 atm			
Flash point	56 °C at 101 kPa closed cup			
Evaporation rate	Not determined			
Flammability (solid, gas)	not relevant, (fluid)			

Explosive limits

- Lower explosion limit (LEL)	0.6 vol%			
- Upper explosion limit (UEL)	4.9 vol%			
Vapor pressure	132 Pa at 25 °C			
Density	not determined			
Vapor density	this information is not available			
Relative density	Information on this property is not available			
Solubility(ies)	not determined			
Partition coefficient				
- n-octanol/water (log KOW)	this information is not available			

acc. to 29 CFR 1910.1200 App D

Schemenauer Distribution Quartz

Date of compilation: 2023-01-12

Auto-ignition temperature	262 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none
Temperature class (USA, acc. to NEC 500)	$\begin{array}{c} T2B \mbox{ (maximum permissible surface temperature on the equipment: $260°C$)} \end{array}$

SECTION 10: Stability and reactivity

10.1 Reactivity

Version number: GHS 1.0

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if swallowed.

acc. to 29 CFR 1910.1200 App D

Schemenauer Distribution Quartz

Version number: GHS 1.0 Date of compilation: 2023-01-12 Г

Acute toxicity estimate (ATE) of components of the mixture				
Name of substance	CAS No	Exposure route	ATE	
Cyclosilazanes, di-Me, Me Hydrogen, polymers with di-Me, Me hydrogen silazanes, and 2,4-TDI	2649792-57-2	oral	500 ^{mg} / _{kg}	
Alkyl Polysilicates	Trade Secret	oral	500 ^{mg} / _{kg}	

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Suspected of damaging fertility.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	lame of substance CAS No Er		Value	Species	Exposure time
octamethylcyclotet- rasiloxane	556-67-2	LC50	>22 ^{µg} / _l	fish	96 h
octamethylcyclotet- rasiloxane	556-67-2	EC50	>1,000 ^{mg} / _l	aquatic invertebrates	96 h
decamethylcyclopentas- iloxane	541-02-6	LC50	>16 ^{µg} / _l	fish	96 h
decamethylcyclopentas- iloxane	541-02-6	EC50	>2.9 ^{µg} / _l	aquatic invertebrates	48 h
Alkyl Polysilicates	Trade Secret	LC50	>934 ^{mg} / _l	fish	96 h
Alkyl Polysilicates	Trade Secret	EC50	331 ^{mg} / _l	aquatic invertebrates	48 h

5

acc. to 29 CFR 1910.1200 App D

Schemenauer Distribution Quartz

Version number: GHS 1.0

Date of compilation: 2023-01-12

Aquatic toxicity (chronic) of components of the mixture

Addate toxicity (chiefino) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
octamethylcyclotet- rasiloxane	556-67-2	LC50	10 ^{µg} /I	fish	14 d
octamethylcyclotet- rasiloxane	556-67-2	EC50	>500 ^{mg} / _l	aquatic invertebrates	24 h
decamethylcyclopentas- iloxane	541-02-6	LC50	>16 ^{µg} / _l	fish	14 d
decamethylcyclopentas- iloxane	541-02-6	EC50	>15 ^{µg} / _l	aquatic invertebrates	21 d
Alkyl Polysilicates	Trade Secret	EC50	43 ^{mg} / _l	microorganisms	5.75 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

The substance fulfills the very bioaccumulative criterion.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

The mixture contains a substance that was identified as a PBT (persistent, bioaccumulative and toxic). The mixture contains a substance that was identified as vPvB (very persistent and very bioaccumulative).

12.6 Endocrine disrupting properties

Contains an endocrine disruptor (EDC) in a concentration of $\ge 0,1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

acc. to 29 CFR 1910.1200 App D

Schemenauer Distribution Quartz

	Schemenauer Dist	
Versior	number: GHS 1.0	Date of compilation: 2023-01-
SEC	TION 14: Transport information	
4.1	UN number	
	DOT	UN 1993
	IMDG-Code	UN 1993
	ICAO-TI	UN 1993
4.2	UN proper shipping name	
	DOT	Flammable liquid, n.o.s.
	IMDG-Code	FLAMMABLE LIQUID, N.O.S.
	ICAO-TI	Flammable liquid, n.o.s.
	Technical name (hazardous ingredients)	octamethylcyclotetrasiloxane, Cyclosilazanes, di-Me Me Hydrogen, polymers with di-Me, Me hydrogen si azanes, and 2,4-TDI
4.3	Transport hazard class(es)	
	DOT	3
	IMDG-Code	3
	ICAO-TI	3
4.4	Packing group	
	DOT	III
	IMDG-Code	III
	ICAO-TI	III
4.5	Environmental hazards	hazardous to the aquatic environment
	Environmentally hazardous substance (aquatic environment)	decamethylcyclopentasiloxane
4.6	Special precautions for user There is no additional information.	
4.7	Transport in bulk according to IMO instruments The cargo is not intended to be carried in bulk.	
	Information for each of the UN Model Regulations	
	Transport of dangerous goods by road or rail (49	—
	Particulars in the shipper's declaration	UN1993, Flammable liquid, n.o.s., (contains: octa- methylcyclotetrasiloxane, Cyclosilazanes, di-Me, Me Hydrogen, polymers with di-Me, Me hydrogen sil- azanes, and 2,4-TDI), 3, III, environmentally hazard ous
	Reportable quantity (RQ)	8,620,690 lbs (3,913,793 kg) (methanol)
	Danger label(s)	3, fish and tree
	Environmental hazards	Yes (hazardous to the aquatic environment)
	Special provisions (SP)	B1, B52, IB3, T4, TP1, TP29

acc. to 29 CFR 1910.1200 App D

Schemenauer Distribution Quartz

International Maritime Dangerous G	Date of compilation: 2023-01
Marine pollutant	Yes (hazardous to the aquatic environment) (decamethylcyclopenta iloxane)
Danger label(s)	3, fish and tree
Special provisions (SP)	223, 274, 955
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-E, <u>S-E</u>
Stowage category	A
International Civil Aviation Organiza	tion (ICAO-IATA/DGR) - Additional information
Environmental hazards	Yes (hazardous to the aquatic environment)
Danger label(s)	3
Special provisions (SP)	A3
Excepted quantities (EQ)	E1
Limited quantities (LQ)	10 L

15.1 Safety, health and environmental regulations specific for the product in question National regulations (United States) Toxic Substance Control Act (TSCA) all ingredients are listed as "ACTIVE"

all ingredients are listed as "ACTIVE"|tous les composants sont énumérés comme "ACTIVE"

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
octamethylcyclotetrasiloxane	556-67-2	solvents	Canada PBiTs CECBP - Priority Chemicals EC PBTs
decamethylcyclopentasiloxane	541-02-6	solvents	Canada PBiTs CECBP - Priority Chemicals EC PBTs
Cyclosilazanes, di-Me, Me Hydrogen, polymers with di-Me, Me hydrogen silazanes, and 2,4- TDI	2649792-57-2	refractory resin	
Alkyl Polysilicates	Trade Secret	resin	
distillates (petroleum) hydrotreated, light	64742-47-8	solvents	

acc. to 29 CFR 1910.1200 App D

Schemenauer Distribution Quartz

Version number: GHS 1.0			Date of compilation: 2023-01-12
Name of substance	CAS No	Functionality	Authoritative Lists
polydimethylsiloxane	63148-62-9	surface modifier	
trimethylsiloxysilicate	68988-56-7	resin	
polytrimethylhydrosilylsiloxane	68988-56-7	surface modifier	
tetra(trimethylsiloxy)silane	3555-47-3	surface modifier	Canada PBiTs
methanol	67-56-1	alcohols	CA TACs NTP OHAT - Repr. or Dev. Toxicants OEHHA RELs Prop 65

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and **Toxic Enforcement Act of 1987**

Proposition 65 List of chemicals					
Name of substance	Name acc. to inventory	CAS No	Wt%	Remarks	Type of the tox- icity
methanol	methanol	67-56-1	0.058		develop- mental

VOC content

- Regulated Volatile Organic Compounds (VOC-EPA)	0.058 %
- Regulated Volatile Organic Compounds (VOC-Cal ARB)	0.058 %

Industry or sector specific available guidance(s) NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperat- ures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperat- ures before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

acc. to 29 CFR 1910.1200 App D

Schemenauer Distribution Quartz

Version number: GHS 1.0

Date of compilation: 2023-01-12

National inventories

Country	Inventory	Status
CA	DSL	not all ingredients are listed
CA	NDSL	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed
AU	AIIC	not all ingredients are listed
CN	IECSC	not all ingredients are listed
EU	ECSI	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	not all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	not all ingredients are listed

Legend

Legena	
AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NDSL	Non-domestic Substances List (NDSL)
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
49 CFR US DOT	49 CFR U.S. Department of Transportation
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
Cal ARB	California Air Resources Board
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level

acc. to 29 CFR 1910.1200 App D

Schemenauer Distribution Quartz

Version number: GHS 1.0

Date of compilation: 2023-01-12

lumber: GHS 1.0	Date of compliation: 2023-01-12
Abbr.	Descriptions of used abbreviations
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protect- ing human health and the environment
ERG No	Emergency Response Guidebook - Number
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HS	Harmonized Commodity Description and Coding System (Harmonized System, drawn up by the World Customs Organisation)
ΙΑΤΑ	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethal- ity during a specified time interval
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
РВТ	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
Repr.	Reproductive toxicity
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture. Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

acc. to 29 CFR 1910.1200 App D

Schemenauer Distribution Quartz

Version number: GHS 1.0

Date of compilation: 2023-01-12

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H227	Combustible liquid.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H361f	Suspected of damaging fertility.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.